

# LINCLAMP SK



Rail size	2 Fixing holes		4 Fixing holes		Low carriage			High carriage							Holding force	Holding force	Mass
	L	L	L1	B	H1	H1	A	H	H1	A	B1	C	G	M	Version 6 bar	Version 4 bar	
Unit	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]			[N]	[N]	[kg]
LC 15 SK	55	61	51	45	24	18	14	-	-	14	5	15	M5	M4	450	300	0.5
LC 20 SK	55	61	51	54	30	22	16	-	-	16	5	20	M5	M6	650	430	0.6
LC 25 SK	55	61	51	75	36	25,5	16	40	29,5	20	5	20	M5	M6	800	530	0.7
LC 30 SK	66,5	78	58,5	82	42	30	21	45	33	24	8,75	22	M5	M8	1150	750	0.9
LC 35 SK	66,5	78	58,5	96	48	35	21,2	55	42	28,2	8,75	24	G1/8	M8	1250	800	1.27
LC 45 SK	80	92	72	116	60	45	27,5	70	55	37,5	10	26	G1/8	M10	1500	950	2
LC 55 SK	100	112	92	136	70	49	30,5	80	59	40,5	10	30	G1/8	M10	2000	1300	2.8

Errors excepted. Only the written order confirmation is valid.

# LINCLAMP SK

