

# ROTOCLAMP OUTSIDE XS ACTIVE



Size	D1 opened rated pressure  Pn = 0 bar	Empfohlene Wellen- durchmesser	D2	D3	B	E	F	n Number of fixing screws	a	t1	t2	Elastic holding torque Pn = 6 bar  at 6 bar	Elastic holding torque Pn = 4 bar  at 4 bar	Mass max.	Air requirement per stroke max.
Unit	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	Quantity	[mm]	[°]	[°]	[Nm]	[Nm]	[kg]	[mL]
Tolerance	-0.02/-0.03	+0.01/+0.025	± 0.1		+0.4										
Roundness	0.01	0.01													
Surface finish	R <sub>a</sub> 0.8 μm	R <sub>a</sub> 0.8 μm													
RCO 110 XSA	110	110	30	15	22	15	15	6xM5	5,5	60	60	125	90	1.5	20

When ordering, please specify »4 bar« or »6 bar« and »with or without booster«. Technical data applies to RotoClamp Outside XS Active. Holding torque for tandem version: Values factor 1.8. Subject to changes and errors, the respective written order confirmation applies.

# ROTOCLAMP OUTSIDE XS ACTIVE

