

ROTOCLAMP OUTSIDE XS STANDARD



Size	D1 opened rated pressure Pn = 4 bar or 6 bar	Required shaft diameter	D2	D3	B	E	F	n Number of fixing screws	a	t1	t2	Elastic holding torque Pn = 6 bar at 0 bar	Elastic holding torque Pn = 6 bar Booster at 6 bar	Elastic holding torque Pn = 4 bar at 0 bar	Elastic holding torque Pn = 4 bar Booster at 4 bar	Mass max.	Luftbedarf pro Hub max.
Unit	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	Quantity	[mm]	[°]	[°]	[Nm]	[Nm]	[Nm]	[Nm]	[kg]	[mL]
Tolerance	-0.02/-0.03	+0.01/+0.025	± 0.1		+0.4												
Roundness	0.01	0.01															
Surface finish	R _a 0.8 μm	R _a 0.8 μm															
RCO 110 XS	110	110	30	15	22	15	15	6xM5	5,5	60	60	125	230	90	150	15	20

When ordering, please specify »4 bar« or »6 bar« and »with or without booster«. Technical data applies to RotoClamp Outside XS Standard. Holding torque for tandem version: Values factor 1.8. Subject to changes and errors, the respective written order confirmation applies.

ROTOCLAMP OUTSIDE XS STANDARD

